

Gamintojas ir modelis			SENDO APOLLO	SENDO APOLLO	SENDO APOLLO	SENDO APOLLO
Gamintojo kodas			SND-09APL2	SND-12APL2	SND-18APL2	SND-24APL2
Tipas			šilumos siurblys	šilumos siurblys	šilumos siurblys	šilumos siurblys
Valdymas			nuotolinis valdymo pultas	nuotolinis valdymo pultas	nuotolinis valdymo pultas	nuotolinis valdymo pultas
Šaldymo galia	W		2600(940~3300)	3400(1000~3770)	5100(1250-5910)	6810(1830~7800)
Šildymo galia	W		2610(940~3360)	3420(1000~3810)	5100(1250-6070)	6870(1850~7900)
SEER	W/W		6.1	6.1	6.1	6.1
Energijos klasė (vid.)			A++	A++	A++	A++
SCOP	W/W		4.0	4.0	4.0	4.0
Energijos klasė (vid.)			A+	A+	A+	A+
Galia prie -10°C temp.	W		1900	2000	3600	4500
SCOP (šildymo režime)	W/W		5.1	5.1	5.1	5.1
Energijos klasė (šildymo režime)			A+++	A+++	A+++	A+++
Kondensato kiekis	Litrai/h		1	1.2	1.5	1.8
Vidinio bloko skleidžiamas garsas (S/H/M/L/Mute)	dB(A)		40/37/33/25/22	40/37/33/25/22	43/41/38/35/27	44/41/38/34/30
Išorinio bloko skleidžiamas garsas (S/H/M/L/Mute)	dB(A)		50/47/43/35/32	50/47/43/35/32	53/50/47/43/36	54/51/48/44/40
Elektros matinimas			220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P
Matinimo privedimas			Išoriniam blokui	Išoriniam blokui	Išoriniam blokui	Išoriniam blokui
Elektros srovė	A		4.0(1.2~8.0)	5.8(1.5~9.0)	8.1(1.7~12.0)	10.7(2.3~12.3)
Maks. Energijos vartojimas	Šaldyme	W	825(240~1380)	1130(290~1500)	1580(330-2340)	2257(410~2824)
	Šildyme	W	767(240~1552)	1005(290~1720)	1374(340-2520)	2063(420~3005)
Freono tipas/kiekis/GWP/CO2 atitikmuo			R32/0.45kg/675/0.304 t	R32/0.49kg/675/0.331 t	R32/1kg/675/0.675 t	R32/1.14kg/675/0.770 t
Kompresorius	Modelis		35W2ALLB9F#MC	35W2ALLB9F#MC	KSN140D33UFZ3	C-6RZ146H3DBF
	Gamintojas		RECHI	RECHI	GMCC	SANYO
Maks. oro kiekis	m <sup>3</sup> /h		420	550	800	980
Signalinis kabelis tarp blokų			4x0.75mm <sup>2</sup>	4x0.75mm <sup>2</sup>	4x0.75mm <sup>2</sup>	4x0.75mm <sup>2</sup>
Pajungimas	Dujos	Coliai	3/8"	3/8"	3/8"	1/2"
	Skystis	Coliai	1/4"	1/4"	1/4"	1/4"
Maks. trasų ilgis	m		25	25	25	25
Maks. Trasų aukščio perkritis	m		10	10	10	10
Veikimo temperatūra	Outdoor	°C	Šaldyme: -15-53 Šildyme: -20-30	Šaldyme: -15-53 Šildyme: -20-30	Šaldyme: -15-53 Šildyme: -20-30	Šaldyme: -15-53 Šildyme: -20-30
Matmenys (P x A x G)	Vidinis	mm	698x255x190	777x250x201	910x294x206	1010x315x220
	Išorinis	mm	712x276x459	712x276x459	853x602x349	920x699x380
Svoris (vidinis/išorinis)	Vidinis	kg	6.5 / 22	7.5 / 22	10 / 35	13 / 40



Auto defrost



Self-diagnosis of faults



Sleep mode



Turbo mode



Auto restart



Timer



Antibacterial function



Self-cleaning function



Air flow up and down



Follow me mode